



SAFETY DATA SHEET

according to Regulation (EU) 2020/878

Page 1/7

ResinVest™

Revision 0
Revision date 2025-01-09

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name ResinVest™

1.2. Relevant identified uses of the substance or mixture and uses advised against

Description Foundry material.

1.3. Details of the supplier of the safety data sheet

Company Ransom & Randolph
Address 3535 Briarfield Boulevard
Maumee, Ohio 43537 USA
Web www.ransom-randolph.com
Telephone +1 (419) 865-9497
Fax +1 (419) 865-9997
Email SDS@ransom-randolph.com
Email address of the competent person rcarter@ransom-randolph.com

1.4. Emergency telephone number

Emergency telephone number USA +1 419 865 9497
Company Ransom & Randolph Co.
08:00-17:00 (US Eastern Std. / GMT minus 5)
For medical advice contact:
NHS 111 in England: 111
NHS 24 in Scotland: 111
NHS Direct in Wales: 111 or 0845 4647

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.2. Classification - EC 1272/2008 Carc. 1A: H350; STOT RE 1: H372;

2.2. Label elements

Hazard pictograms



This substance / mixture has been classified in accordance with the US Federal OSHA Hazard Communication Standard 29CFR 1910.1200. Substance concentration band-ranges are presented, and minor ingredient composition maybe withheld, to protect trade secrets.

ResinVest™

Revision 0
Revision date 2025-01-09

2.2. Label elements

Signal Word	Danger
Hazard Statement	Carc. 1A: H350 - May cause cancer inhalation. STOT RE 1: H372 - Causes damage to organs (lungs) through prolonged or repeated exposure inhalation.
Precautionary Statement: Prevention	P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood. P260 - Do not breathe dust/fume/gas/mist/vapours/spray. P264 - Wash (hands) thoroughly after handling. P270 - Do not eat, drink or smoke when using this product. P280 - Wear protective gloves/protective clothing/eye protection/face protection. P285 - In case of inadequate ventilation wear respiratory protection.
Precautionary Statement: Response	P308+P313 - IF exposed or concerned: Get medical advice/attention. P314 - Get medical advice/attention if you feel unwell.
Precautionary Statement: Storage	P405 - Store locked up.
Precautionary Statement: Disposal	P501 - Dispose of contents/container to local and national regulations

2.3. Other hazards

Other hazards	Product contains crystalline silica.
---------------	--------------------------------------

Further information

	Not applicable. PBT and vPvB assessment.
--	--

SECTION 3: Composition/information on ingredients

3.2. Mixtures

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
monomagnesium phosphate		7757-86-0			1 - 10%	Skin Irrit. 2: H315; Eye Irrit. 2: H319;
quartz (conc. >= 1.0%)		14808-60-7	238-878-4		50 - 60%	Carc. 1A: H350; STOT RE 1: H372;
silica (cristobalite conc. >= 1.0%)		14464-46-1	238-455-4		1 - 10%	Carc. 1A: H350; STOT RE 1: H372;

Particle Characteristics

	Full text for all Risk Phrases mentioned in this section are displayed in Section 16.
--	---

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air.
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open.
Skin contact	Wash with soap and water.
Ingestion	Drink 1 to 2 glasses of water. DO NOT INDUCE VOMITING.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	May cause irritation to respiratory system.
Eye contact	May cause irritation to eyes.
Skin contact	May cause irritation to skin.

ResinVest™

Revision 0
Revision date 2025-01-09

4.2. Most important symptoms and effects, both acute and delayed

Ingestion	May cause irritation to mucous membranes.
-----------	---

4.3. Indication of any immediate medical attention and special treatment needed

Inhalation	Seek medical attention if irritation or symptoms persist.
Eye contact	Seek medical attention if irritation or symptoms persist.
Skin contact	Seek medical attention if irritation or symptoms persist.
Ingestion	Seek medical attention if irritation or symptoms persist.

SECTION 5: Firefighting measures

5.1. Extinguishing media

	Use extinguishing media appropriate to the surrounding fire conditions.
--	---

5.2. Special hazards arising from the substance or mixture

	Burning produces irritating, toxic and obnoxious fumes.
--	---

5.3. Advice for firefighters

	Self-contained breathing apparatus. Wear suitable protective clothing.
--	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

	Avoid raising dust. Wear suitable respiratory equipment when necessary.
--	---

6.2. Environmental precautions

	No environmental requirements.
--	--------------------------------

6.3. Methods and material for containment and cleaning up

	Avoid raising dust. Clean the area using a vacuum cleaner. Transfer to suitable, labelled containers for disposal.
--	--

6.4. Reference to other sections

	See section for further information.
--	--------------------------------------

SECTION 7: Handling and storage

7.1. Precautions for safe handling

	Avoid raising dust. Ensure adequate ventilation of the working area. In case of insufficient ventilation, wear suitable respiratory equipment.
	Do not eat, drink or smoke in areas where this product is used or stored. Wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

	Keep containers tightly closed.
--	---------------------------------

7.3. Specific end use(s)

	Foundry material.
--	-------------------

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

	exposure limits: total Crystalline Silica (quartz plus cristobalite) - 0.025 mg/m ³ TWA ACGIH TLV (respirable fraction); 50 ug/m ³ 8 hr -TWA PEL (respirable fraction).
--	---

ResinVest™

Revision 0
Revision date 2025-01-09

8.2. Exposure controls

8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection measures	Protective clothing.
Eye / face protection	In case of splashing, wear: Approved safety goggles. safety glasses with side-shields.
Skin protection - Handprotection	Wear suitable gloves.
Respiratory protection	Suitable respiratory equipment.
8.2.3. Environmental exposure controls	Not normally required.
Occupational exposure controls	Appropriate local exhaust ventilation is required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Powder
Colour	Off white
Odour	Odourless
pH	Not applicable.
Melting point	Not applicable.
Freezing Point	Not applicable.
Initial boiling point	Not applicable.
Flash point	Not applicable.
Evaporation rate	Not applicable.
Flammability (solid, gas)	Not applicable.
Vapour Flammability	Not applicable.
Upper Explosive Limit	Not applicable.
Lower Explosive Limit	Not applicable.
Vapour pressure	Not applicable.
Relative Vapour Density	Not applicable.
Density / Relative Density	Not applicable.
Water solubility	Not applicable.
Fat Solubility	Not applicable.
Partition coefficient (n-octanol/water)	Not applicable.
Partition coefficient	Not applicable.
Autoignition temperature	Not applicable.
Viscosity	Not applicable.
Explosive properties	Not applicable.
Oxidising properties	Not applicable.

9.2. Other information

Softening point	Not applicable.
Gas group	Not applicable.
Benzene Content	Not applicable.
Lead content	Not applicable.
VOC (Volatile organic compounds)	Not applicable.

ResinVest™

Revision 0
Revision date 2025-01-09**SECTION 10: Stability and reactivity****10.1. Reactivity**

Not applicable.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No Significant Hazard.

10.4. Conditions to avoid

Moisture.

10.5. Incompatible materials

No Significant Hazard.

10.6. Hazardous decomposition products

Hazardous Decomposition Products (silica): Crystalline silica will dissolve in hydrofluoric acid and produce silicone tetrafluoride. Reaction with water or acids generates heat.

SECTION 11: Toxicological information**11.1 Information on hazard classes**

Acute toxicity	Based on available data, the classification criteria are not met.
Skin corrosion/irritation	Prolonged or repeated exposure may cause irritation to skin and mucous membranes.
Serious eye damage/irritation	If eye irritation persists: Get medical advice/attention.
Respiratory or skin sensitisation	No sensitization effects reported.
Germ cell mutagenicity	No mutagenic effects reported.
Carcinogenicity	Known Human Carcinogens (Category 1).
Reproductive toxicity	No observed effect level. No observed effect concentration.
STOT-single exposure	No known adverse health effects.
STOT-repeated exposure	<p>Chronic effects</p> <p>Prolonged inhalation of respirable crystalline silica</p> <p>In 1997, the International Agency for Research on Cancer (IARC) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However it pointed out that not all industrial circumstances, nor all crystalline silica types, were to be incriminated. (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibers, 1997, Vol. 68, IARC, Lyon, France). In June 2003, the European Commission's Scientific Committee for Occupational Exposure Limits (SCOEL) concluded:</p> <p>"that the main effect in humans of the inhalation of respirable crystalline silica is silicosis. There is sufficient information to conclude that the relative lung cancer risk is increased in persons with silicosis (and apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk. Since a clear threshold for silicosis development cannot be identified, any reduction of exposure will reduce the risk of silicosis."</p> <p>(SCOEL SUM Doc 94-final on respirable crystalline silica, June 2003)</p> <p>There is a body of evidence supporting the fact that increased cancer risk would be limited to people already suffering from silicosis. Worker protection against silicosis should be assured by respecting the existing regulatory occupational exposure limits and implementing additional risk management measures where required (see Section 16).</p>

ResinVest™

Revision 0
Revision date 2025-01-09

11.1 Information on hazard classes

Aspiration hazard	No Significant Hazard.
Repeated or prolonged exposure	Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system.

SECTION 12: Ecological information

12.2. Persistence and degradability

	No data is available on this product.
--	---------------------------------------

12.3. Bioaccumulative potential

	Does not bioaccumulate.
--	-------------------------

Partition coefficient

	ResinVest™ Not applicable.
--	----------------------------

12.4. Mobility in soil

	Not determined.
--	-----------------

12.5. Results of PBT and vPvB assessment

	Not determined.
--	-----------------

12.7 Other adverse effects

	Not applicable.
--	-----------------

SECTION 13: Disposal considerations

13.1. Waste treatment methods

	Dispose of in compliance with all. local and national regulations.
--	--

Disposal methods

	Contact a licensed waste disposal company.
--	--

Disposal of packaging

	Empty containers can be sent for disposal or recycling.
--	---

SECTION 14: Transport information

Further information

	The product is not classified as dangerous for carriage.
--	--

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulations	<p>U.S. FEDERAL REGULATIONS: Bio-Vest investment. CERCLA 103 Reportable Quantity: is not subject to CERCLA reporting requirements. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.</p> <p>SARA TITLE III: Hazard Category For Section 311/312: Chronic health</p> <p>Section 313 Toxic Chemicals: This product contains the following chemicals subject to Annual Release Reporting Requirements Under SARA Title III, Section 313 (40 CFR 372): None</p> <p>Section 302 Extremely Hazardous Substances (TPQ): None</p>
-------------	--

ResinVest™

Revision 0
Revision date 2025-01-09

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EPA Toxic Substances Control Act (TSCA) Status: All of the components of this product are listed on the TSCA inventory.

U.S. STATE REGULATIONS

California Proposition 65: This product contains the following substances known to the State of California to cause cancer: Crystalline Silica as Quartz and Cristobalite (> 90%)

INTERNATIONAL REGULATIONS:

Canadian Environmental Protection Act: All of the components in this product are listed on the Domestic Substances List (DSL).

Canadian WHMIS Classification: Class D Division 2A.

15.2. Chemical safety assessment

No data is available on this product.

SECTION 16: Other information

Other information

Text of Hazard Statements in Section 3

Skin Irrit. 2: H315 - Causes skin irritation.
Eye Irrit. 2: H319 - Causes serious eye irritation.
Carc. 1A: H350 - May cause cancer .
STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure .

Further information

Training
Workers must be informed of the presence of crystalline silica and trained in the proper use and handling of this product as required under applicable regulations.

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.