

SAFETY DATA SHEET

according to Regulation (EU) 2020/878

Page 1/7

Plasticast (R) PT investment

Revision 1
Revision date 2024-02-09

SECTION 1: Identification of the substance/mixture and of th	ne compan	y/undertaking
--	-----------	---------------

1.1. Product identifier

Web

Product name Plasticast (R) PT investment

1.2. Relevant identified uses of the substance or mixture and uses advised against

Description Foundry material.

1.3. Details of the supplier of the safety data sheet

Company Ransom & Randolph

Address 3535 Briarfield Boulevard

Maumee, Ohio 43537 USA www.ransom-randolph.com

USA +1 419 865 9497

Telephone +1 (419) 865-9497

Fax +1 (419) 865-9997

Email SDS@ransom-randolph.com
Email address of the rcarter@ransom-randolph.com

1.4. Emergency telephone number

Emergency telephone number

competent person

Company Ransom & Randolph Co.

08:00-17:00 (US Eastern Std. / GMT minus 5)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.2. Classification - EC 1272/2008

Carc. 1A: H350; STOT RE 1: H372;

2.2. Label elements

This substance / mixture has been classified in accordance with the US Federal OSHA Hazard Communication Standard 29CFR 1910.1200. Substance concentration band-ranges are presented, and minor ingredient composition maybe withheld, to protect trade secrets.

Hazard pictograms



Signal Word

Hazard Statement

Danger

Carc. 1A: H350 - May cause cancer inhalation.

STOT RE 1: H372 - Causes damage to organs (lungs) through prolonged or repeated exposure

Revision 1 Revision date 2024-02-09

2.2. Label elements

	inhalation.		
Precautionary Statement:	P201 - Obtain special instructions before use.		
Prevention	P202 - Do not handle until all safety precautions have been read and understood.		
	P260 - Do not breathe dust/fume/gas/mist/vapours/spray.		
	P264 - Wash (hands) thoroughly after handling.		
	P270 - Do not eat, drink or smoke when using this product.		
	P280 - Wear protective gloves/protective clothing/eye protection/face protection.		
	P285 - In case of inadequate ventilation wear respiratory protection.		
Precautionary Statement:	P308+P313 - IF exposed or concerned: Get medical advice/attention.		
Response	P314 - Get medical advice/attention if you feel unwell.		
Precautionary Statement:	P405 - Store locked up.		
Storage			
Precautionary Statement:	P501 - Dispose of contents/container to local and national regulations		
Disposal			
2.3. Other hazards			
Other hazards	Product contains crystalline silica.		
Further information			

SECTION 3: Composition/information on ingredients

3.2. Mixtures

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
silica (cristobalite conc. >/= 1.0 %)		14464-46-1	238-455-4		40 - 50%	Carc. 1A: H350; STOT RE 1: H372;
quartz (conc. >/= 1.0%)		14808-60-7	238-878-4		30 - 40%	Carc. 1A: H350; STOT RE 1: H372;

Not applicable. PBT and vPvB assessment.

Particle Characteristics

Full text for all Risk Phrases mentioned in this section are displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air.	
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open.	
Skin contact	Wash with soap and water.	
Ingestion	Drink 1 to 2 glasses of water. DO NOT INDUCE VOMITING.	

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	May cause irritation to respiratory system.	
Eye contact	May cause irritation to eyes.	
Skin contact	May cause irritation to skin.	
Ingestion	May cause irritation to mucous membranes.	

4.3. Indication of any immediate medical attention and special treatment needed

4.5. Indication of any immediate medical attention and special treatment needed			
Inhalation Seek medical attention if irritation or symptoms persist.			
Eye contact	Seek medical attention if irritation or symptoms persist.		

Revision 1 Revision date 2024-02-09

4.3. Indication of any immediate	medical attention and special treatment needed
Skin contact	Seek medical attention if irritation or symptoms persist.
Ingestion	Seek medical attention if irritation or symptoms persist.
SECTION 5: Firefighting mea	asures
5.1. Extinguishing media	
	Use extinguishing media appropriate to the surrounding fire conditions.
5.2. Special hazards arising from	the substance or mixture
	Burning produces irritating, toxic and obnoxious fumes.
5.3. Advice for firefighters	
	Self-contained breathing apparatus. Wear suitable protective clothing.
SECTION 6: Accidental relea	ase measures
6.1. Personal precautions, protect	ctive equipment and emergency procedures
	Avoid raising dust. Wear suitable respiratory equipment when necessary.
6.2. Environmental precautions	
	No environmental requirements.
6.3. Methods and material for co	ntainment and cleaning up
	Avoid raising dust. Clean the area using a vacuum cleaner. Transfer to suitable, labelled containers for disposal.
6.4. Reference to other sections	
	See section for further information.
SECTION 7: Handling and st	orage
7.1. Precautions for safe handling	g
	Avoid raising dust. Ensure adequate ventilation of the working area. In case of insufficient ventilation, wear suitable respiratory equipment.
	Do not eat, drink or smoke in areas where this product is used or stored. Wash hands after handling the product.
7.2. Conditions for safe storage,	including any incompatibilities
	Keep containers tightly closed.
7.3. Specific end use(s)	
	Foundry material.
SECTION 8: Exposure contro	ols/personal protection
8.1. Control parameters	
	exposure limits: total Crystalline Silica (cristobalite plus quartz) - 0.025 mg/m3 TWA ACGIH TLV (respirable fraction); 50 ug/m3 8-hr TWA PEL (respirable fraction).
	exposure limits: total Crystalline Silica (quartz plus cristobalite) - 0.025 mg/m3 TWA ACGIH TLV (respirable fraction); 50 ug/m3 8 hr -TWA PEL (respirable fraction).
8.2. Exposure controls	
8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.

Revision 1 Revision date 2024-02-09

8.2. Exposure controls

8.2.2. Individual protection	Protective clothing.
measures	
Eye / face protection	In case of splashing, wear:. Approved safety goggles. safety glasses with side-shields.
Skin protection -	Wear suitable gloves.
Handprotection	
Respiratory protection	Suitable respiratory equipment.
8.2.3. Environmental exposure	Not normally required.
controls	
Occupational exposure	Appropriate local exhaust ventilation is required.
controls	

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Powder
Colour	Off white
Odour	Slight
Density / Relative Density	2.38 (H2O = 1 @ 20 °C)
Partition coefficient	No data available
pH	No data available
Melting point	No data available
Viscosity	No data available
Explosive properties	Not applicable.
Oxidising properties	Not applicable.
Freezing Point	Not applicable.
Initial boiling point	Not applicable.
Evaporation rate	Not applicable.
Flammability (solid, gas)	Not applicable.
Vapour pressure	Not applicable.
Relative Vapour Density	Not applicable.
Autoignition temperature	Not applicable.
Fat Solubility	Not applicable.
Solubility	Slightly soluble in water

9.2. Other information

Conductivity	No data available
Surface tension	Not applicable.
Lead content	Not applicable.
VOC (Volatile organic	Not applicable.
compounds)	
Benzene Content	Not applicable.

SECTION 10: Stability and reactivity

10.1. Reactivity

	Not applicable.	
10.2. Chemical stability		
	Stable under normal conditions.	

Revision 1
Revision date 2024-02-09

10.3. Possibility of hazardous reactions		
	No Significant Hazard.	
10.4. Conditions to avoid		
	Moisture.	
10.5. Incompatible materials		
	No Significant Hazard.	
10.6. Hazardous decomposition products		
	Hazardous Decomposition Products (silica): Crystalline silica will dissolve in hydrofluoric acid and produce silicone tetrafluoride. Reaction with water or acids generates heat.	
SECTION 44: Toyloglarian i		

SECTION 11: Toxicological information

11.1 Information on hazard classes

Skin corrosion/irritation
Serious eye damage/irritation
Respiratory or skin
sensitisation
Germ cell mutagenicity
Carainagenicity

Germ cell mutagenicity
Carcinogenicity
Reproductive toxicity

STOT-single exposure STOT-repeated exposure

Acute toxicity

Based on available data, the classification criteria are not met.

Prolonged or repeated exposure may cause irritation to skin and mucous membranes.

No irritation expected.

No sensitizaton effects reported.

No mutagenic effects reported.

Known Human Carcinogens (Category 1).

No observed effect level. No observed effect concentration.

No known adverse health effects.

Chronic effects

Prolonged inhalation of respirable crystalline silica

In 1997, the International Agency for Research on Cancer (IARC) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However it pointed out that not all industrial circumstances, nor all crystalline silica types, were to be incriminated. (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibers, 1997, Vol. 68, IARC, Lyon, France). In June 2003, the European Commission's Scientific Committee for Occupational Exposure Limits (SCOEL) concluded:

"that the main effect in humans of the inhalation of respirable crystalline silica is silicosis. There is sufficient information to conclude that the relative lung cancer risk is increased in persons with silicosis (and apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk. Since a clear threshold for silicosis development cannot be identified, any reduction of exposure will reduce the risk of silicosis."

(SCOEL SUM Doc 94-final on respirable crystalline silica, June 2003)

There is a body of evidence supporting the fact that increased cancer risk would be limited to people already suffering from silicosis. Worker protection against silicosis should be assured by respecting the existing regulatory occupational exposure limits and implementing additional risk management measures where required (see Section 16).

Aspiration hazard Repeated or prolonged exposure No Significant Hazard.

Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system.

SECTION 12: Ecological information

12.2. Persistence and degradability

Revision 1 Revision date 2024-02-09

	11000001 ddb 2021 02 00
12.2. Persistence and degrada	bility
	No data is available on this product.
12.3. Bioaccumulative potentia	I
	Does not bioaccumulate.
Partition coefficient	
	Plasticast (R) PT investment No data available
12.4. Mobility in soil	
	Not determined.
12.5. Results of PBT and vPvB	sassessment
	Not determined.
12.7 Other adverse effects	·
	Not applicable.
SECTION 13: Disposal con	siderations
13.1. Waste treatment methods	5
	Dispose of in compliance with all. local and national regulations.
Disposal methods	
	Contact a licensed waste disposal company.
Disposal of packaging	
	Empty containers can be sent for disposal or recycling.
SECTION 14: Transport info	ormation
Further information	
	The product is not classified as dangerous for carriage.
SECTION 15: Regulatory in	nformation
15.1. Safety, health and environ	nmental regulations/legislation specific for the substance or mixture
Regulations	U.S. FEDERAL REGULATIONS: Plasticast PT investment CERCLA 103 Reportable Quantity: is not subject to CERCLA reporting requirements. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.
	SARA TITLE III: Hazard Category For Section 311/312: Chronic health
	Section 313 Toxic Chemicals: This product contains the following chemicals subject to Annual Release Reporting Requirements Under SARA Title III, Section 313 (40 CFR 372): None
	Section 302 Extremely Hazardous Substances (TPQ): None
	EPA Toxic Substances Control Act (TSCA) Status: All of the components of this product are listed on the TSCA inventory.

U.S. STATE REGULATIONS

Revision 1
Revision date 2024-02-09

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture California Proposition 65: This product contains the following substances known to the State of California to cause cancer: Crystalline Silica as Quartz and Cristobalite (< 90 %); INTERNATIONAL REGULATIONS: Canadian Environmental Protection Act: All of the components in this product are listed on the Domestic Substances List (DSL). Canadian WHMIS Classification: Class D2A (Chronic toxic effects), D2A (Carcinogenicity). 15.2. Chemical safety assessment No data is available on this product. SECTION 16: Other information Other information **Text of Hazard Statements in** Carc. 1A: H350 - May cause cancer . Section 3 STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure . **Further information Training** Workers must be informed of the presence of crystalline silica and trained in the proper use and handling of this product as required under applicable regulations. The information supplied in this Safety Data Sheet is designed only as guidance for the safe use,