Neycraft™ Multizone™
duplicating unit



The Neycraft Multizone duplicating unit offers precision and reliability, with customizable programming, smart capabilities, and advanced built-in safety features.

Features

- Innovative and user-friendly units capable of meeting changing needs as workflow increases and decreases.
- Possesses smart capabilities to work with variable capacities.
- Features a lid safety magnet to prevent fire, damage, and injury.
- Allows complete user temperature control, allowing the user to adjust the melting temperature, idle temperature, and hold time manually or via the R&R Duplicator Connect app (preferred).
- Offers precise and reliable operation as well as an automated power-saving on/off feature for an extended motor life.
- A Quick Start Guide is included to help you get your machine ready to use via the R&R Duplicator Connect App.

What Fits Your Workflow

Neycraft Multizone Duplicating Units

Capacity	Voltage	Current	Power	Frequency	Weight	Dimensions
1, 2, or 3 gal	120V	13.5 A	1620 W	50/60 Hz	75 lbs.	24” L x 16” W x 22” D
1, 2, or 3 gal	230V	8.5 A	2040 W	50/60 Hz	75 lbs.	24” L x 16” W x 22” D
1 – 5 gal	230V	8.5 A	2040 W	50/60 Hz	83 lbs.	29” L x 16” W x 22” D

**These results are based on the testing methods, frequency and procedures of Ransom & Randolph or its approved suppliers. The levels referenced herein are only for general guidance and do not constitute a firm specification.*

Availability

3 gallon unit (Melts 1, 2, or 3 gallons of material)
120V.....535631000
230V.....535632000

5 gallon unit (Melts up to 5 gallons of material)
230V.....535652000

To order, visit Shop.Ransom-Randolph.com, contact your region’s R&R Customer Service Team, or contact an authorized distributor. For a list of authorized distributors, visit Ransom-Randolph.com/Distributors.

Rev. 2026-11-04

R&R Ransom&Randolph

USA Office
3535 Briarfield Boulevard
Maumee, Ohio 43537
1.800.800.7496 | 419.865.9497

European Office
Leipziger Straße 40
04571 Rötha Germany
+49 342 06373999