

SAFETY DATA SHEET

according to Regulation (EU) 2015/830

Page 1/8

Kwik-Core (TM) powder

Revision 2 **Revision date** 2020-09-18

I	SECTION 1: I	Identification of	the substance/mixture	e and of the co	mpany/undertaking
ı					

1.1. Product identifier

Product name Kwik-Core (TM) powder [NA]

1.2. Relevant identified uses of the substance or mixture and uses advised against

Description Foundry material.

1.3. Details of the supplier of the safety data sheet

Company Ransom & Randolph

Address 3535 Briarfield Boulevard, PO Box 1570

Maumee, Ohio 43537 USA

Web www.ransom-randolph.com

Telephone +1 (419) 865-9497 +1 (419) 865-9997 Fax

Email RR.SDS@dentsply.com Email address of the RR.SDS@dentsply.com

1.4. Emergency telephone number

USA +1 419 865 9497 **Emergency telephone number**

Ransom & Randolph Co. Company

08:00-17:00 (US Eastern Std. / GMT minus 5)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.2. Classification - EC 1272/2008

Carc. 1A: H350; STOT RE 1: H372;

2.2. Label elements

competent person

This substance / mixture has been classified in accordance with the US Federal OSHA Hazard Communication Standard 29CFR 1910.1200. Substance concentration band-ranges are presented, and minor ingredient composition maybe withheld, to protect trade secrets.

Hazard pictograms



Signal Word

Hazard Statement Carc. 1A: H350 - May cause cancer inhalation.

Danger

STOT RE 1: H372 - Causes damage to organs (lungs) through prolonged or repeated exposure

inhalation.

Precautionary Statement: Prevention

P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P260 - Do not breathe dust/fume/gas/mist/vapours/spray.

Revision 2
Revision date 2020-09-18

2 5	2 1	ahe	ام اد	lem	۵n	te
Z.	6 . L	aux	71 C			ш

Z.Z. Label elements	
	P264 - Wash (hands) thoroughly after handling. P270 - Do no eat, drink or smoke when using this product. P280 - Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary Statement: Response Precautionary Statement:	P285 - In case of inadequate ventilation wear respiratory protection. P308+P313 - IF exposed or concerned: Get medical advice/attention. P314 - Get medical advice/attention if you feel unwell. P405 - Store locked up.
Storage Precautionary Statement: Disposal	P501 - Dispose of contents/container to local and national regulations
2.3. Other hazards	
Other hazards	Product contains crystalline silica. This material contains trace amounts of naturally occurring uranium, thorium, and radium.
Further information	
	Not applicable. PBT and vPvB assessment.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
silica, viterous Overall product (Silica, fused respirable dust)		60676-86-0	262-373-8		30 - 40%	
quartz (conc. >/= 1.0%)		14808-60-7	238-878-4		10 - 20%	Carc. 1A: H350; STOT RE 1: H372;
silica (cristobalite conc. >/= 1.0 %)	14464-46-1	238-455-4		1 - 10%	Carc. 1A: H350; STOT RE 1: H372;
quartz (conc. < 1.0%)		14808-60-7	238-878-4		0 - 0.5%	Carc. 1A: H350;
Silica (cristobalite) >/= 0.1 % conc. < 1.0 %		14464-46-1	238-455-4		0 - 0.5%	Carc. 1A: H350;

Further information

Full text for all Risk Phrases mentioned in this section are displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air.	
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open.	
Skin contact Wash with soap and water.		
Ingestion	Drink 1 to 2 glasses of water. DO NOT INDUCE VOMITING.	

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	May cause irritation to respiratory system.	
Eye contact	May cause irritation to eyes.	
Skin contact	May cause irritation to skin.	
Ingestion	May cause irritation to mucous membranes.	

4.3. Indication of any immediate medical attention and special treatment needed

Inhalation	Seek medical attention if irritation or symptoms persist.
Eye contact	Seek medical attention if irritation or symptoms persist.
Skin contact	Seek medical attention if irritation or symptoms persist.

Revision 2 Revision date 2020-09-18

4.3. Indication of any immediate	medical attention and special treatment needed
Ingestion	Seek medical attention if irritation or symptoms persist.
SECTION 5: Firefighting me	asures
5.1. Extinguishing media	
	Use extinguishing media appropriate to the surrounding fire conditions.
5.2. Special hazards arising from	n the substance or mixture
	Burning produces irritating, toxic and obnoxious fumes.
5.3. Advice for firefighters	
	Self-contained breathing apparatus. Wear suitable protective clothing.
SECTION 6: Accidental relea	ase measures
6.1. Personal precautions, prote	ctive equipment and emergency procedures
	Avoid raising dust. Wear suitable respiratory equipment when necessary.
6.2. Environmental precautions	
	No environmental requirements.
6.3. Methods and material for co	ontainment and cleaning up
	Avoid raising dust. Clean the area using a vacuum cleaner. Transfer to suitable, labelled containers for disposal.
6.4. Reference to other sections	
	See section [2, 8 & 13] for further information.
SECTION 7: Handling and s	torage
7.1. Precautions for safe handlir	ng
	Avoid raising dust. Ensure adequate ventilation of the working area. In case of insufficient ventilation, wear suitable respiratory equipment.
	Do not eat, drink or smoke in areas where this product is used or stored. Wash hands after handling the product.
7.2. Conditions for safe storage,	including any incompatibilities
	Keep containers tightly closed.
7.3. Specific end use(s)	
	Foundry material.
SECTION 8: Exposure contr	ols/personal protection
8.1. Control parameters	
<u> </u>	
	exposure limits - Silica, vitreous (fused, amorphous) 80 mg/m3 / (% Silica), TWA PEL (respirable fraction).
	exposure limits - Crystalline Silica, Cristobalite - 0.025 mg/m3 TWA ACGIH TLV (respirable fraction); 50 ug/m3 8-hr TWA PEL (respirable fraction).
	exposure limits - Crystalline Silica, quartz - 0.025 mg/m3 TWA ACGIH TLV (respirable fraction); 50 ug/m3 8 hr -TWA PEL (respirable fraction).
	exposure limits - Zirconium silicate 10 mg/m3 STEL ACGIH (respirable fraction) 5 mg/m3 TWA OSHA PEL (respirable fraction).
8 1 1 Evnosure Limit Values	

8.1.1. Exposure Limit Values

Revision 2
Revision date 2020-09-18

8.1.1. Exposure Limit Values

silica, viterous Overall	WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m3: 0.08
product (Silica, fused respirable		
dust)		
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: -
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	inhalable dust:	inhalable dust:
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	respirable dust:	respirable dust:

8.2. Exposure controls

8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection	Protective clothing.
measures	
Eye / face protection	In case of splashing, wear:. Approved safety goggles. safety glasses with side-shields.
Skin protection -	Wear suitable gloves.
Handprotection	
Respiratory protection	Suitable respiratory equipment.
8.2.3. Environmental exposure	Not normally required.
controls	
Occupational exposure	Appropriate local exhaust ventilation is required.
controls	

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Powder
Colour	Off white
Odour	Slight
pН	4 - 7
Relative density	3.6 (H2O = 1 @ 20 °C)
Partition coefficient	No data available
Melting point	No data available
Viscosity	No data available
Explosive properties	Not applicable.
Oxidising properties	Not applicable.
Freezing Point	Not applicable.
Initial boiling point	Not applicable.
Evaporation rate	Not applicable.
Vapour pressure	Not applicable.
Vapour density	Not applicable.
Autoignition temperature	Not applicable.
Fat Solubility	Not applicable.
Solubility	Slightly soluble in water

9.2. Other information

Conductivity	No data available
Surface tension	No data available
Lead content	No data available
VOC (Volatile organic	
compounds)	
Gas group	Not applicable.
Benzene Content	Not applicable.
Benzene Content	Not applicable.

Revision 2
Revision date 2020-09-18

SECTION 10: Stability and reactivity		
10.1. Reactivity		
	Not applicable.	
10.2. Chemical stability		
	Stable under normal conditions.	
10.3. Possibility of hazardous reactions		
	No Significant Hazard.	
10.4. Conditions to avoid		
	Moisture.	
10.5. Incompatible materials		
	No Significant Hazard.	
10.6. Hazardous decomposition products		
	Hazardous Decomposition Products (silica): Crystalline silica will dissolve in hydrofluoric acid and produce silicone tetrafluoride. Reaction with water or acids generates heat.	
	Hazardous Decomposition Products (Zircon): Zirconium silicate will disassociate to Zirconium Dioxide (ZRO2) and Silicon dioxide (SiO2) when heated above 1540 degrees Celsius. Hazardous Polymerization: Will not occur.	

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	Based on available data, the classification criteria are not met.
Skin corrosion/irritation	Prolonged or repeated exposure may cause irritation to skin and mucous membranes.
Serious eye damage/irritation	No irritation expected.
Respiratory or skin	No sensitizaton effects reported.
sensitisation	
Germ cell mutagenicity	No mutagenic effects reported.
Carcinogenicity	Known Human Carcinogens (Category 1).
Reproductive toxicity	No observed effect level. No observed effect concentration.
STOT-single exposure	No known adverse health effects.
STOT-repeated exposure	Chronic effects
	Prolonged inhalation of respirable crystalline silica
	In 1997, the International Agency for Research on Cancer (IARC) concluded that crystalline silica
	inhaled from occupational sources can cause lung cancer in humans. However it pointed out that

In 1997, the International Agency for Research on Cancer (IARC) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However it pointed out that not all industrial circumstances, nor all crystalline silica types, were to be incriminated. (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibers, 1997, Vol. 68, IARC, Lyon, France). In June 2003, the European Commission's Scientific Committee for Occupational Exposure Limits (SCOEL) concluded:

"that the main effect in humans of the inhalation of respirable crystalline silica is silicosis. There is sufficient information to conclude that the relative lung cancer risk is increased in persons with silicosis (and apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk. Since a clear threshold for silicosis development cannot be identified, any reduction of exposure will reduce the risk of silicosis."

(SCOEL SUM Doc 94-final on respirable crystalline silica, June 2003)

There is a body of evidence supporting the fact that increased cancer risk would be limited to people already suffering from silicosis. Worker protection against silicosis should be assured by respecting the existing regulatory occupational exposure limits and implementing additional risk management measures where required (see Section 16).

Revision 2 Revision date 2020-09-18

11.1. Information on toxicologica	al effects
Aspiration hazard	This product contains trace quantities of naturally occurring radioactive uranium, thorium and radium (106-120 Picocuries/gram). Overexposure to respirable dust containing radioactive materials may cause lung cancer. Zirconium silicate is exempt from NRC regulations for source material per 10 CFR 40, since it falls under the definition of material containing less than 0.05% uranium or thorium. However, calculations show that observance of 2-2.8 mg/m3 of respirable dust will, under voluntary guidelines, ensure that intake is less than 10% of the annual limits on intake (ALS) specified in 10 CFR 20.1502(B) and NRC Standards for the protection against radiation for uranium, thorium, radium and radioactive daughter decay products.). No Significant Hazard.
Repeated or prolonged	Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system.
exposure	initial attorning cause cougning, lightness of the chest and initiation of the respiratory system.
SECTION 12: Ecological info	ormation
12.2. Persistence and degradab	
Talai i ololotolloo alla abgladab	No data is available on this product.
12.3. Bioaccumulative potential	
·	
	Does not bioaccumulate.
Partition coefficient	
	Kwik-Core (TM) powder No data available
	[NA]
12.4. Mobility in soil	
	Not determined.
12.5. Results of PBT and vPvB	assessment
	Not determined.
12.6. Other adverse effects	·
	Not applicable.
SECTION 13: Disposal cons	iderations
13.1. Waste treatment methods	
	Dispose of in compliance with all. local and national regulations.
Disposal methods	
	Contact a licensed waste disposal company.
Disposal of packaging	
	Empty containers can be sent for disposal or recycling.
SECTION 14: Transport info	rmation
14.1. UN number	
	The product is not classified as dangerous for carriage.
14.2. UN proper shipping name	
	The product is not classified as dangerous for carriage.
14.3. Transport hazard class(es))
	The product is not classified as dangerous for carriage.
14.4. Packing group	
	The product is not classified as dangerous for carriage.

Revision 2
Revision date 2020-09-18

The product is not classified as dangerous for carriage.

14.6. Special precautions for user

The product is not classified as dangerous for carriage.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

The product is not classified as dangerous for carriage.

Further information

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulations

U.S. FEDERAL REGULATIONS: Kwik-Core™ investment. CERCLA 103 Reportable Quantity: is not subject to CERCLA reporting requirements. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations. SARA TITLE III:

Hazard Category For Section 311/312: Chronic health

The product is not classified as dangerous for carriage.

Section 313 Toxic Chemicals: This product contains the following chemicals subject to Annual Release Reporting Requirements Under SARA Title III, Section 313 (40 CFR 372): None

Section 302 Extremely Hazardous Substances (TPQ): None

EPA Toxic Substances Control Act (TSCA) Status: All of the components of this product are listed on the TSCA inventory.

U.S. STATE REGULATIONS

California Proposition 65: This product contains the following substances known to the State of California to cause cancer: Crystalline Silica as Quartz and Cristobalite (< 25%)

INTERNATIONAL REGULATIONS:

Canadian Environmental Protection Act: All of the components in this product are listed on the Domestic Substances List (DSL).

Canadian WHMIS Classification: Class D Division 2A

European Inventory of New and Existing Chemicals Substances (EINECS): All of the components in this product are listed on the EINECS inventory.

Australian Inventory of Chemical Substances: All of the components in this product are listed on the AICS for Australia.

China Inventory of Existing Chemicals and Chemical Substances: All of the components in this product are listed on the IECSC for China.

Japanese Existing and New Chemical Substances: All of the components in this product are listed on the Japanese ENCS list.

Korean Existing Chemicals List: All of the components in this product are listed on the KECL for Korea.

Philippine Inventory of Chemicals and Chemical Substances: All of the components in this product are listed on the PICCS.

15.2. Chemical safety assessment

No data is available on this product.

SECTION 16: Other information

Other information

RevisionThis document differs from the previous version in the following areas:.

Revision 2 Revision date 2020-09-18

Other information		
	2 - 2.1. Classification of the substance or mixture.	
	15 - Labelling.	
	15 - Hazard Statement.	
	15 - Safety phrases.	
Text of Hazard Statements in	Carc. 1A: H350 - May cause cancer .	
Section 3	STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure .	
Further information		
	Training Workers must be informed of the presence of crystalline silica and trained in the proper use and handling of this product as required under applicable regulations.	
	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.	