SAFETY DATA SHEET

according to 29 CFR 1910.1200 and GHS

READYBUILT Intermediate

Revision 0

Revision date 2026-10-14

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	READYBUILT Intermediate

1.2. Relevant identified uses of the substance or mixture and uses advised against

Description	Foundry material.

1.3. Details of the supplier of the safety data sheet

Company	Ransom & Randolph
Address	3535 Briarfield Boulevard Maumee, Ohio 43537 USA
Web	www.ransom-randolph.com
Telephone	+1 (419) 865-9497
Fax	+1 (419) 865-9997
Email	SDS@ransom-randolph.com
Email address of the competent person	rcarter@ransom-randolph.com

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.2. Classification - GHS	Carc. 1A: H350;

2.2. Label elements

Hazard pictograms	This substance / mixture has been classified in accordance with the US Federal OSHA Hazard Communication Standard 29CFR 1910.1200. Substance concentration band-ranges are presented, and minor ingredient composition maybe withheld, to protect trade secrets. 
Signal Word	Danger
Hazard Statement	Carc. 1A: H350 - May cause cancer inhalation. .
Precautionary Statement: Prevention	P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood. P280 - Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary Statement: Response	P308+P313 - IF exposed or concerned: Get medical advice/attention.
Precautionary Statement: Storage	P405 - Store locked up.
Precautionary Statement: Disposal	P501 - Dispose of contents/container to local and national regulations

Copyright © 2026 ChemSoft. All rights reserved.

Powered by ChemSoft EH&S

READYBUILT Intermediate

Revision 0
Revision date 2026-10-14

2.3. Other hazards

Other hazards	This LIQUID product contains less than one-percent (<1%) crystalline silica. . . Amorphous silica may be converted to crystalline silica (cristobalite) when subjected to very high temperatures (1700° F). Exposure to respirable crystalline silica may cause lung disease. . . This material contains trace amounts of naturally occurring uranium, thorium, and radium.

Further information

	Not applicable. PBT and vPvB assessment.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
silica, viterous		60676-86-0	262-373-8		50 - 60%	
quartz (conc. >/= 1.0%) (Silica, Crystalline-a-Quartz and Cristobalite)		14808-60-7	238-878-4		0 - 0.5%	Carc. 1A: H350; STOT RE 1: H372;
quartz (conc. < 1.0%) (Silica, Crystalline-a-Quartz and Cristobalite)		14808-60-7	238-878-4		0.5 - 1%	Carc. 1A: H350;

Particle Characteristics

	Full text for all Risk Phrases mentioned in this section are displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air.
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open.
Skin contact	Wash with soap and water.
Ingestion	Drink 1 to 2 glasses of water. DO NOT INDUCE VOMITING.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	May cause irritation to respiratory system.
Eye contact	May cause irritation to eyes.
Skin contact	May cause irritation to skin.
Ingestion	May cause irritation to mucous membranes.

4.3. Indication of any immediate medical attention and special treatment needed

Inhalation	Seek medical attention if irritation or symptoms persist.
Eye contact	Seek medical attention if irritation or symptoms persist.
Skin contact	Seek medical attention if irritation or symptoms persist.
Ingestion	Seek medical attention if irritation or symptoms persist.

SECTION 5: Firefighting measures

5.1. Extinguishing media

	Use extinguishing media appropriate to the surrounding fire conditions.

5.2. Special hazards arising from the substance or mixture

	Burning produces irritating, toxic and noxious fumes.

5.3. Advice for firefighters

	Self-contained breathing apparatus. Wear suitable protective clothing.

SECTION 6: Accidental release measures

Copyright © 2026 ChemSoft. All rights reserved.

Powered by ChemSoft EH&S

READYBUILT Intermediate

6.1. Personal precautions, protective equipment and emergency procedures

	Avoid raising dust. Wear suitable respiratory equipment when necessary.

6.2. Environmental precautions

	No environmental requirements.

6.3. Methods and material for containment and cleaning up

	Avoid raising dust. Clean the area using a vacuum cleaner. Transfer to suitable, labelled containers for disposal.

6.4. Reference to other sections

	See section for further information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

	Avoid raising dust. Ensure adequate ventilation of the working area. In case of insufficient ventilation, wear suitable respiratory equipment. . . Do not eat, drink or smoke in areas where this product is used or stored. Wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

	Keep containers tightly closed.

7.3. Specific end use(s)

	Foundry material.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

	exposure limits: Silica, vitreous (fused, amorphous) 80 mg/m3 / (% Silica), TWA PEL (respirable fraction). . . exposure limits: total Crystalline Silica (quartz plus cristobalite) - 0.025 mg/m3 TWA ACGIH TLV (respirable fraction); 50 ug/m3 8 hr -TWA PEL (respirable fraction). . . exposure limits: Zirconium silicate 10 mg/m3 STEL ACGIH (respirable fraction) 5 mg/m3 TWA OSHA PEL (respirable fraction).

8.2. Exposure controls

	
Appropriate engineering controls	Ensure adequate ventilation of the working area.
Individual protection measures	Protective clothing.
Eye / face protection	In case of splashing, wear:. Approved safety goggles. safety glasses with side-shields.
Skin protection - Hand protection	Wear suitable gloves.
Respiratory protection	Suitable respiratory equipment.
8.2.3. Environmental exposure controls	Not normally required.
Occupational exposure controls	Appropriate local exhaust ventilation is required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Copyright © 2026 ChemSoft. All rights reserved.

Powered by ChemSoft EH&S

READYBUILT Intermediate

9.1. Information on basic physical and chemical properties

State	Viscous liquid.
Color	Yellow
Odor	Slight
pH	9 - 11
Melting point	Not applicable.
Freezing Point	≈ 0 °C
Initial boiling point	No data available
Evaporation rate	No data available
Vapor pressure	No data available
Relative Vapour Density	No data available
Density / Relative Density	1.2 - 1.8 (H2O = 1 @ 20 °C)
Fat Solubility	Not applicable.
Partition coefficient	No data available
Viscosity	No data available
Solubility	Miscible in water

9.2. Other information

Conductivity	No data available
Surface tension	No data available
Gas group	Not applicable.
Benzene Content	Not applicable.
Lead content	Not applicable.
VOC (Volatile organic compounds)	Not applicable.

SECTION 10: Stability and reactivity

10.1. Reactivity

Not applicable.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No Significant Hazard.

10.4. Conditions to avoid

Moisture.

10.5. Incompatible materials

No Significant Hazard.

10.6. Hazardous decomposition products

Hazardous Decomposition Products (silica): Crystalline silica will dissolve in hydrofluoric acid and produce silicone tetrafluoride. Reaction with water or acids generates heat. . . Hazardous Decomposition Products (Zircon): Zirconium silicate will disassociate to Zirconium Dioxide (ZRO2) and Silicon dioxide (SiO2) when heated above 1540 degrees Celsius. Hazardous Polymerization: Will not occur.

SECTION 11: Toxicological information

11.1 Information on hazard classes

Acute toxicity	Based on available data, the classification criteria are not met.
Skin corrosion/irritation	Prolonged or repeated exposure may cause irritation to skin and mucous membranes.
Serious eye damage/irritation	No irritation expected.

Copyright © 2026 ChemSoft. All rights reserved.

Powered by ChemSoft EH&S

READYBUILT Intermediate

11.1 Information on hazard classes

Respiratory or skin sensitization	No sensitizaton effects reported.
Germ cell mutagenicity	No mutagenic effects reported.
Carcinogenicity	Known Human Carcinogens (Category 1).
Reproductive toxicity	No observed effect level. No observed effect concentration.
STOT-single exposure	No known adverse health effects.
STOT-repeated exposure	Chronic effects Prolonged inhalation of respirable crystalline silica In 1997, the International Agency for Research on Cancer (IARC) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However it pointed out that not all industrial circumstances, nor all crystalline silica types, were to be incriminated. (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibers, 1997, Vol. 68, IARC, Lyon, France). In June 2003, the European Commission's Scientific Committee for Occupational Exposure Limits (SCOEL) concluded: "that the main effect in humans of the inhalation of respirable crystalline silica is silicosis. There is sufficient information to conclude that the relative lung cancer risk is increased in persons with silicosis (and apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk. Since a clear threshold for silicosis development cannot be identified, any reduction of exposure will reduce the risk of silicosis." (SCOEL SUM Doc 94-final on respirable crystalline silica, June 2003) There is a body of evidence supporting the fact that increased cancer risk would be limited to people already suffering from silicosis. Worker protection against silicosis should be assured by respecting the existing regulatory occupational exposure limits and implementing additional risk management measures where required (see Section 16). . . This product contains trace quantities of naturally occurring radioactive uranium, thorium and radium (106-120 Picocuries/gram). Overexposure to respirable dust containing radioactive materials may cause lung cancer. Zirconium silicate is exempt from NRC regulations for source material per 10 CFR 40, since it falls under the definition of material containing less than 0.05% uranium or thorium. However, calculations show that observance of 2-2.8 mg/m3 of respirable dust will, under voluntary guidelines, ensure that intake is less than 10% of the annual limits on intake (ALS) specified in 10 CFR 20.1502(B) and NRC Standards for the protection against radiation for uranium, thorium, radium and radioactive daughter decay products.).
Aspiration hazard	No Significant Hazard.
Repeated or prolonged exposure	Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system.

11.1.4. Toxicological information

	not determined

SECTION 12: Ecological information

12.1. Toxicity

	not determined

12.2. Persistence and degradability

	No data is available on this product.

12.3. Bioaccumulative potential

	Does not bioaccumulate.

Partition coefficient

	READYBUILT Intermediate No data available

Copyright © 2026 ChemSoft. All rights reserved.

Powered by ChemSoft EH&S

READYBUILT Intermediate

12.4. Mobility in soil	
	not determined.

12.5. Results of PBT and vPvB assessment	
	not determined.

12.7 Other adverse effects	
	Not applicable.

SECTION 13: Disposal considerations

13.1. Waste treatment methods	
	Dispose of in compliance with all. local and national regulations.

Disposal methods	
	Contact a licensed waste disposal company.

Disposal of packaging	
	Empty containers can be sent for disposal or recycling.

SECTION 14: Transport information

14.1. UN number	
	The product is not classified as dangerous for carriage.

14.2. UN proper shipping name	
	The product is not classified as dangerous for carriage.

14.3. Transport hazard class(es)	
	The product is not classified as dangerous for carriage.

14.4. Packing group	
	The product is not classified as dangerous for carriage.

14.5. Environmental hazards	
	The product is not classified as dangerous for carriage.

14.6. Special precautions for user	
	The product is not classified as dangerous for carriage.

14.7 Maritime Transport in bulk according to IMO instruments	
	The product is not classified as dangerous for carriage.

Further information	
	The product is not classified as dangerous for carriage.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture	
Regulations	U.S. FEDERAL REGULATIONS: CERCLA 103 Reportable Quantity: Not subject to CERCLA reporting requirements. Many states have more stringent release reporting requirements. Report spills required under federal, state, and local regulations. SARA TITLE III: Hazard Category for Section 311/312: None Section 313 Toxic Chemicals: This product contains the following chemicals subject to Annual Release Reporting Requirements under SARA Title III, Section 313 (40 CFR 372): None Section 302 Extremely Hazardous Substances (TPQ): None EPA Toxic Substances Control Act (TSCA) Status: All of the components of this product are listed

Copyright © 2026 ChemSoft. All rights reserved.

Powered by ChemSoft EH&S

READYBUILT Intermediate

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

	on the TSCA inventory. U.S. STATE REGULATIONS: California Proposition 65: This product contains the following substances known to the State of California to cause cancer: Quartz <1% INTERNATIONAL REGULATIONS: Canadian Environmental Protection Act: All of the components in this product are listed on the Domestic Substances List (DSL).

15.2. Chemical safety assessment

	No data is available on this product.

SECTION 16: Other information

Other information

Text of Hazard Statements in Section 3	Carc. 1A: H350 - May cause cancer . STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure .

Further information

	Training Workers must be informed of the presence of crystalline silica and trained in the proper use and handling of this product as required under applicable regulations. . . The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.

Copyright © 2026 ChemSoft. All rights reserved.

Powered by ChemSoft EH&S